



HLXS.EX28547 - Butterfly Valves

Butterfly Valves

Ani Enterprises Group Pty Ltd
 52b Lara Way
 Campbellfield, VIC 3061 Australia

EX28547

Model	Size, NPS	Body Type	Pressure Rating, psig (Bar)	Indicator Post	Supervisory Switch*
Butterfly valve					
AV-BF-GG300	2, 2.5(76.1mm), 2.5, 3, 4, 5, 5 (139.7 mm), 6, 6 (165.1 mm)	Groove	300	—	I/O
	8, 8 (216.3 mm), 10, 10 (267.4 mm)			—	I/O
	12, 12 (318.4 mm)			—	I/O
AV-BF-WF300	2, 2.5, 3, 4, 5, 6	Wafer	300	—	I/O
	8, 10			—	I/O
	12			—	I/O

Note: F-Flange, G-Groove

* I = Indoor installation; O = Outdoor installation

Last Updated on 2021-05-17

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

Cookies on UL

We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners. [Learn more](#)

Cookies Settings

Accept All Cookies