



# HMRZ.EX28548 - Gate Valves

## Gate Valves

Ani Enterprises Group Pty Ltd  
 52b Lara Way  
 Campbellfield, VIC 3061 Australia

EX28548

Model	Type	Size, in.	Rated Pressure, psig	Rated Pressure, psig End Configuration
AV-OG-FF300	O.S&Y	2.5,3,4,5,6,8,10,12	300	Flange & Flange
AV-OG-FG300	O.S&Y	2.5,3,4,5,6,8,10,12	300	Flange & Grooved
AV-OG-GG300	O.S&Y	2.5,3,4,5,6,8,10,12	300	Grooved & Grooved
AV-OG-FF300A	O.S&Y	2.5,3,4,5,6,8,10,12	300	Flange & Flange
AV-OG-FG300A	O.S&Y	2.5,3,4,5,6,8,10,12	300	Flange & Grooved
AV-OG-GG300A	O.S&Y	2.5,3,4,5,6,8,10,12	300	Grooved & Grooved
AV-NG-FF300	NRS	2.5,3,4,5,6,8,10,12	300	Flange & Flange
AV-NG-FG300	NRS	2.5,3,4,5,6,8,10,12	300	Flange & Grooved
AV-NG-GG300	NRS	2.5,3,4,5,6,8,10,12	300	Grooved & Grooved
AV-NG-FF300A	NRS	2.5,3,4,5,6,8,10,12	300	Flange & Flange
AV-NG-GG300A	NRS	2.5,3,4,5,6,8,10,12	300	Grooved & Grooved
AV-NG-FG300A	NRS	2.5,3,4,5,6,8,10,12	300	Flange & Grooved
AV-OG-FF200	O.S&Y	2,2.5,3,4,5,6,8,10,12	200	Flange & Flange
AV-OG-FG200				Flange & Grooved
AV-OG-GG200				Grooved & Grooved
AV-NG-FF200	NRS	2.5,3,4,5,6,8,10,12	200	Flange & Flange
AV-NG-FG200				Flange & Grooved
AV-NG-GG200				Grooved & Grooved

Note: O.S&Y, outside-screw-and-yoke type; NRS, non-rising stem type.

Flanges comply with ASME/ANSI B16.1 Class 125, or ASME/ANSI B16.42 Class 150, or BS EN1092-2, or GB/T9113.1; Grooves comply with AWWA C606; Mechanical Joints comply with ANSI/AWWA C110 and ANSI/AWWA C153.

For 300 psi, use Face flange, for 200 psi, use Raised-face flange.

Last Updated on 2021-04-28

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"

### Cookies on UL

We use cookies to personalize content and ads, to provide social media features and to analyze our traffic. We also share information about your use of our site with our social media, advertising and analytics partners. [Learn more](#)

Cookies Settings

Accept All Cookies